

A large graphic consisting of several overlapping circles. One circle is solid light gray, another is solid white, and a third is filled with black and white diagonal stripes. To the right, there are several curved, overlapping lines in shades of gray and white, suggesting motion or a stylized wave.

**ADHESIVE
EPOXY
GROUT**

**TILE JOINT
FILLER**

Bonding Trust with Every Product.



NSA-CT-1

APPLICATION AREA

For installing 300x450mm
300x600mm tiles on wall
600x600mm tiles on floor.

Packing : Available in 20kg



SUPER
STRONG



PREMIUM
PRODUCT



DAMP
APPLICATION



HEAT
RESISTANT



LOW
CONSUMPTION



NSA-SVT-2

APPLICATION AREA

For Installing 600x600mm
600x1200mm On Wall
Up To 10 Feet, 800x800mm
800x1600mm On Floor.
It Suitable For Tile On Tile.

Packing : Available in 20kg



SUPER
STRONG



PREMIUM
PRODUCT



DAMP
APPLICATION



HEAT
RESISTANT



LOW
CONSUMPTION





NSA-BVT-3



APPLICATION AREA

It Suitable To Use For Large-format Vitrified Tiles On Wall | Granite Window Framing. Up To 30 Feet. (For Interior & Exterior Use)

Packing : Available in 20kg



SUPER STRONG



PREMIUM PRODUCT



DAMP APPLICATION



HEAT RESISTANT



LOW CONSUMPTION



NSA-SGT-4



APPLICATION AREA

No Limit Grade. It Suitable To Use For Large-format Vitrified Tiles | Natural Stones | Italian Marble | Granite | Swimming Pool. (For Interior & Exterior Use)

Packing : Available in 20kg



SUPER STRONG



PREMIUM PRODUCT



DAMP APPLICATION



HEAT RESISTANT



LOW CONSUMPTION





WALL PUTTY

APPLICATION AREA

It Provides A Smooth, Even Surface By Filling Cracks, Holes, And Uneven Textures, Ensuring Better Adhesion And A More Polished Finish For Paint.

Packing : Available in 40kg



BLOCK JOINING MORTAR

APPLICATION AREA

It Ensures Strong Adhesion Between Blocks, Provides Better Load Distribution, And Helps With Thermal And Sound Insulation.

Packing : Available in 40kg



EPOXY



Product Features
 Stainless and easy to clean.
 Easy to mix and apply.
 Provides excellent chemical resistant property.

Available In
 1kg | 5 kg

Available in three part & two part
 (Resin, Hardener and filler).
 Available in variants 20+ shades.

Tile Grout Colours

Available In : 1kg



White



Ivory



Teracotta



Grey



Black



R.Brown



Yellow



S. Blue



C.Brown



Pink



Beige



Magenta



O.Green



N.Grey



GROUT ADMIX

MAIN USE

For good joints in all types of tiles and stone grout.

Packing : Available in 200ml



PU ADHESIVE

MAIN USE

Used in most diverse surface like plywood, metal, dry walls, glass, cement sheet, T.V. unit gypsum.

Packing : Available in 4kg



TILE CLEANER

MAIN USE

Removes tough spots and stains from the tiles surface.

Packing : Available in 1Ltr.



01 OT - WHITE




02 OT - IVORY



03 OT - BLACK




04 OT - LIGHT GREY



05 OT - TERRACOTTA



06 OT - R. BROWN




07 OT - YELLOW



08 OT - BLUE



09 OT - C. BROWN



10 OT - PINK



11 OT - BEIGE



12 OT - MAGENTA




13 OT - O. GREEN



14 OT - BURGUNDY



15 OT - DARK GREY




16 OT - APRICOT



17 OT - DENIM



18 OT - SEPIA



19 OT - SKY BLUE



20 OT - LIGHT GREEN



21 OT - ANCHOR



22 OT - PEARL



23 OT - DUST ROSE



24 OT - NAVY BLUE



25 OT - BRONZE




26 OT - PLATINUM



27 OT - MASHROOM




28 OT - NATURAL GREY



29 OT - RED



30 OT - STEEL GREY





SILVER SPARKLE

101 OT - SILVER BLACK



103 OT - SILVER GREY



102 OT - SILVER BROWN



105 OT - SILVER RED



GOLD SPARKLE

201 OT - GOLD BLACK



203 OT - GOLD GREY



202 OT - GOLD BROWN



205 OT - GOLD RED



COPPER SPARKLE

301 OT - COPPER BLACK



303 OT - COPPER GREY



302 OT - COPPER BROWN



305 OT - COPPER RED




SPECIAL

110 OTTAWA - SILVER



310 OTTAWA - COPPER



210 OTTAWA - GOLD



410 OTTAWA 24K- GOLD



Approximate Sq.ft Coverage Per 1 Kg Epoxy Grout

TILE SIZE	JOINT WIDTH							
	in mm	2mm	3 mm	4mm	6mm	8mm	10mm	12mm
100x100x3 mm		52	35	26	18	13	11	9
150x160x4 mm		58	39	29	20	15	12	10
200x150x5 mm		52	35	27	18	13	11	9
150x300x6 mm		62	41	31	20	16	13	11
300x300x6 mm		78	52	39	26	20	16	13
450x300x7 mm		81	54	40	27	20	16	13
600x450x8 mm		101	67	50	34	25	20	17
600x600x8 mm		118	78	59	39	29	23	19
600x900x11 mm		103	68	51	34	25	20	17
900x900x12 mm		118	78	59	39	29	23	19

Approximate Sq.ft Coverage Per 5 Kg Epoxy Grout

TILE SIZE	JOINT WIDTH							
	in mm	2mm	3 mm	4mm	6mm	8mm	10mm	12mm
100x100x3 mm		264	177	133	90	65	55	46
150x160x4 mm		296	198	149	100	75	61	51
200x150x5 mm		269	181	136	91	69	55	46
150x300x6 mm		263	175	132	88	66	53	44
300x300x6 mm		394	263	198	132	100	80	67
450x300x7 mm		405	270	202	135	101	81	68
600x450x8 mm		506	337	253	169	127	101	85
600x600x8 mm		591	394	295	197	148	119	99
600x900x11 mm		515	343	258	171	129	103	86
900x900x12 mm		590	393	295	197	148	118	99

TROWEL



MAIN USE
For spreading all types of tile adhesives.

TILE SPACER



MAIN USE
Maintains an even expansion gap when installing flooring.

TILE EQUILIZER



MAIN USE
For leveling large size tiles.

SIZE

Available in 2, 3, 4, 5, 6, 8 & 10mm



OTTAWA VITRIFIED LLP



+91 97251 44445



CORPORATE OFFICE ADDRESS :
604-6th Floor, Bilva Trade Hub, Mahendranagar Chowkdi,
Pipli Jetapar Road, Morbi-363642 (Guj.) India



ottawaceramic@gmail.com

www.ottawaceramic.in